



Construction

Brass Body (CuZn38Pb18)

Finishes

Black Matt

Product Type

Contemporary

Water Pressure

Min. 0.5 bar, Max. 6.0 bar

Plumbing Systems

Suitable for all plumbing systems, preferably balanced. Min. supply pressure differential requirement is 5:1

Standards

Complies with BSEN 1111

Cartridge

Thermostatic

Valve

Integrate diverter ceramic valve

Check valve

0.5-10 gpm

Fitting

S-Union

Guarantee

10 years against manufacturing faults (3 Years on Serviceable Parts).

Additional Information

1. Temperature: Pre-set 38°C, with push button override to 48°C.
2. Automatic shut off in the event of hot or cold water supply failure.
3. Shower head : 250mm, SS304, Air Induction Thin Head
4. Shower handset : Chrome , 3 mode, ABS
5. Shower hose : PVC easy clean hose, 1.5m.
6. Stainless steel adjustable riser rail.

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
MLSHBE2	-	3.3	-	6.5	10.3	-	-	18.9	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.